SPECIFICATION/S:

Item Num ber	Description	Quan tity	Tot al	Delivered, Weeks/M onths	Item Num ber
	TOURIST FIRST AID BOOTH				
	BOOTH WITH LED LIGHT				
	BOOTH AREA:1.44 sq.m. (1.20m x 1.20m)				
	SYSTEM BOX AREA: 0.72 sq.m. (0.60m x 1.20m)				
	ROOF APEX HEIGHT: 2.60m CEILING HEIGHT: 2.10m				
	Body Material: Robust galvanized metal body Door and				
	Window - vandal-proof tempered glass				
	SOLAR PANEL				
	550w Monocrystalline Panels – 2 sets				
	1.2kw HYBRID INVERTER 24v – 1 unit				
	LITHIUM BATTERY 24v/250ah – 1 unit				
	5m x 6" ϕ Galvanized prefabricated Solar Post with pesdestal – 1 unit	1 lot			
	CCTV CAMERA				
	One Unit PTZ Camera				
	4MP Starlight IR Network PTZ Camera				
	> 1/2.8" 4Megapixel STARVIS™ CMOS.				
	> Starlight technology.				
	> Max. 25/30 fps@2560 × 1440.				
	> IR distance up to 300 m.				
	> Auto tracking 3.0.				
	> Perimeter protection.				
	> Video Metadata.				

> SMD 4.0 > IP66. ONE VIDEO ENCODER WITH TWO-WAY VOICE **COMMUNICATION** Image Sensor - 1/3" 4Megapixel progressive scan CMOS Effective Pixels - 2688(H) x 1520 Scanning System – Progressive Minimum Illumination - 0.08Lux/F2.0(Color,1/3s,30IRE), 0.3Lux/2.0(Color,1/30s,30IRE), 0Lux/F2.0(IR on) S/N Ratio - More than 50dB IR Distance - Distance up to 30m (98ft) IR On/Off Control - Auto/ Manual Lens Type – Fixed Mount Type – Board-in Focal Length - 2.8mm (3.6mm, 6mm optional) Max. Aperture - F2.0 (F2.0, F2.0) Angle of View - H: 104° (83°, 55°), V: 55° (45°, 31°) Pan/Tilt/Rotation Range - Pan:0°~20°; Tilt:±15°; Rotation:0°~360° Compression - H.265+/H.265/H.264+/H.264 Resolution - 4M(2688×1520)/3M(2304×1296)/ 1080P(1920×1080)/1.3M(1280x960)/ 720P(1280×720)/D1(704×576/704×480)/ VGA(640×480)/CIF(352×288/352×240) Frame Rate - 1~25/30fps Digital Zoom – 16x Protocol - HTTP; HTTPs; TCP; ARP; RTSP; RTP; UDP;

SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS;

UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP;

SNMP

Interoperability - ONVIF, PSIA, CGI

Power Supply - -AS: DC12V, PoE (802.3af)(Class 0)

M12: PoE (802.3af)(Class 0)

Operating Conditions - -40° C \sim +70° C (-40° F \sim +158° F)

/ Less than 95% RH

Ingress Protection - IP67,IP6K9K

Vandal Resistance – IK10

Two-Way Voice Communication

Must Stream as low as 50kbps

DATA SIM FOR ONE (1) YEAR

AUTOMATED EXTERNAL DEFIBRILLATOR (AED)

AED cabinet w/ alarm and alert light with lockset and

complete accessories

Waveform: Scope Biphasic

Charge Hold Time: 30 Seconds

Energy Selection: Automatic Programmed Selection

Charge Time: Less than 12 seconds with new batteries

Size: (H X W X D) 8.0" x 7.25" x 1.9"; 20cm x 18.4cm x

4.8cm

Weight: 1.1kg

Battery Type: Lithium Manganese Dioxide

ECG Recording Time: 90 Minutes I

P Rating: IP 56

Battery Life: 4 years

Electrode pad Life: 4 years

Warranty: 8 years		
Falling Height: 1 Meter		
STRETCHER		
Foldable Stretcher with bag 214 x 54 x 13cm 150 kg capacity		
Strengthen by 2 Aluminum alloy steel bars Light weight		
Made of high-quality PVC sheets (fireproof & water repellant)		
Foldable and portable		
FIRST AID KIT (MINIMUM EXPIRATION OF 1 YEAR FROM DELIVERY DATE)		
Insulated First Aid Cabinet		
a. Sterile gauze pads of various sizes		
b. Adhesive tape		
c. Adhesive bandages or band-aids in several sizes		
d. Elastic bandage		
e. Splint		
f. Antiseptic wipes		
g. Soap		
h. Antibiotic ointment		
i. The antiseptic solution, like hydrogen peroxide		
j. Hydrocortisone cream (1%)		
k. Acetaminophen and ibuprofen		
I. First Aid medicines		
m. Tweezers		
n. Sharp scissors		
o. Safety pins		
	<u> </u>	l

	ı	1	1	1
p. Disposable instant cold packs				
q. Calamine lotion				
r. Alcohol wipes or ethyl alcohol				
s. Thermometer				
t. Tooth preservation kit				
u. Plastic non-latex gloves (at least 2 pairs)				
v. Flashlight and additional batteries				
w. Blanket				
x. Mouthpiece for giving CPR from your local Red Cross office				
y. Eye drops				
z. Itch-Stopping Gel				
aa. Sunblock				
1.80m \times 1.20m \times 0.10m Thk. Reinforced Concrete platform w / Foundation included				
COMMAND CENTER	1 lot			
		1		
1 SET OF WORKSTATION				
2mx2m low office partition with built-in table complete with				
accessories and electrical accessories, wires, lighting and outlets				
Heavy duty midback office chairs				
2 units of mobile pedestal cabinet				
VIDEO STREAMING WORKSTATION				
At least with minimum specification:				
Processor: Intel i7 10th				
Generation Memory: 16GB RAM				
Storage: 1TB Solid State Drive				
	<u> </u>	1	<u> </u>	1

Graphics: 2GB Video Graphics		
Windows Operating System		
At least 22' Monitor with keyboard & mouse		
VIDEO STREAMING LICENSE		
55 INCHES TV MONITOR		
At least with minimum specification:		
55 inches screen size		
Resolution: 4K (3840 x 2160)		
Refresh Rate: 60Hz		
Input: HDMI, USB, Ethernet		
Wi-fi compatible		
VESA: 200 x 200mm or 400 x 400mm		
Speaker: 2CH speaker		
UINTERRUPTED POWER SUPPLY (UPS)		
Output Power: 700 Watts / 1000VA		
Nominal Output Voltage: 230V		
Output Voltage Distortion: less than 5%		
Output Frequency: 50/60Hz		
Waveform: Sine wave		
ONE YEAR PAID INTERNET SUBSCRIPTION - BOOTH AND COMMAND CENTER		
50MBPS DEDICATED FIBER CONNECTION		
Linearies		
Locations:		

1. Boracay		
Island, Malay,		
Aklan		
2 Panalas		
2. Panglao,		
Bohol		
3. Siargao		
Island, Surigao		
del Norte		
4 Coron		
4. Coron,		
Palawan		
5. Puerto		
Galera,		
Oriental		
Mindoro		
······································		
Duration: 180 CD		